QUALITY ACCEPTANCE INSPECTION CHECKLIST – GRANDSTANDS/BLEACHERS

(Subject to modifications when required due to change in requirements)

Purchase Order (PO) #:	ITEM DESCRIPTION:	
VENDOR NAME:	LOCATION:	

			Yes	No	N/A
Are adequate bearings provided so that structure bears uniformly on the floor or ground?					
Are all anchor points present and secured per spec	cifications?				
Are bleachers free from corrosion on supports, flo	orboards, and s	eating?			
For outdoor installations, are all components weat	her resistant?				
Are all weld joints free of cracks and penetrations?)				
Are all braces installed and secured per specifications?					
Are all nuts and bolts torqued to the correct specifications?					
Are all plank and rail ending caps installed and sec	ure?				
Are all footboards and walking surfaces non-skid?					
If chain link fabric is used on guardrails, does fabric have a mesh size of 1.75 in ² or less?					
Does construction conform to NFPA Standard 102?					
Is space underneath seating free of flammable and combustible materials, unless space contains an approved, electrically supervised sprinkler system?					
For indoor seating without backs, are seat	s spaced at leas	t 22" back-to-back?			
Is the depth of footboards and seat boards	s at least 9"?				
If the same level is not used for both seat foundations and footrests, are independent footrests independent of seats provided?					
Are all seats and footboards securely fastened?					
If individual seats or chairs are installed, are they secured in rows by fastening individually to the floor or together in groups of three or more seats?					
Does maximum number of seats between	farthest seat ar	d an aisle not exceed:			
Application	Outdoors	Indoors			
Grandstands (seats with backs)	11	6			
Bleachers	20	9			
Where seats are more than 48" above ground level, are guardrails provided along those portions of the backs and ends, and are guardrails at least 42" above the aisle surface or 36" above the seat board (whichever is adjacent)?					
Guardrails are not required where an adjacent	t wall or fence aff	ords equivalent safeguard.			

	Yes	No	N/A
Where the front footrest is more than 24" above ground level, are guardrails at least 33" above such footrests?			
If the front row of seats includes backrests, the height requirement is reduced to 26".			
Do cross aisles located within the seating area have rails at least 26" high along the front edge of the cross aisle?			
If the backs of the seats in front of cross aisle are at least 24" above surface of the cross aisle, guardrails are not required.			
Are vertical openings between guardrails and footboards/seat boards such that a 4" sphere cannot pass through the opening?			
Are openings between the seat board and footboard that are more than 30" above the ground such that a 4" sphere cannot pass through the opening?			

Fold	Folding/Telescopic Seating			
	he space between the back of each seat and the front of each seat behind it at st 12"?			
	ndividual chair-type seats are installed, are they secured in groups of not less in three?			

Any nonconformances found during the inspection shall be repaired by the Vendor, at their cost, prior to passing inspection.